

MODEL

GC2698 系列

筒式综合送料平缝机

Cylinder bed compound feed lockstitch sewing machine

- GC2698-1
- GC2698-1B
- GC2698-2
- GC2698-1D
- GC2698-1N
- GC2698-1BN
- GC2698-1Z



GC2698-1 筒式综合送料平缝机

本系列机型设计采用小筒形缝台，综合送料，同步式移动包边装置。机器外观设计新颖，操作调节方便，缝纫线迹美观均衡，工作效率出众。由于小直径筒形缝台，广泛应用于各类薄型皮具、皮革服装生产、制鞋、座椅垫子加工。适用于衣服、包袋、皮具的缝纫及制鞋、包袋、座垫生产中的滚边工序。

GC2698-1B 型采用 1.4 倍线量旋梭。

GC2698-2 型采用综合送料（椭圆式下送料）。适用于手提袋、鞋类与其他筒型物品的一般缝纫。

GC2698-1D 自动剪线单针筒式综合送料平缝机

GC2698-1N（不含同步式移动包边装置）

GC2698-1BN（大旋梭 不含同步式移动包边装置）

GC2698-1Z 直驱一体式筒式综合送料平缝机

This model is designed with small radius cylinder bed, compound feed mechanism and synchronized binder. It features a novel appearance, easy sewing operations, nice and even stitches and high productivity. With the small radius tubular bed, it is available in binding operation for leather garment, case & bag, shoes, seat cushion, etc.

GC2698-1B uses 1.40 times capacity hook.


GC2698-2 is designed with compound feed (elliptical drop feed) mechanism, available for stitching hand bags, shoes and other tubular articles.

GC2698-1D single-needle cylinder bed compound feed lockstitcher with thread trimmer.

GC2698-1N (without synchronized binder)

GC2698-1BN (1.4 times capacity hook, without synchronized binder)

GC2698-1Z Integrated direct drive cylinder bed compound feed lockstitch sewing machine



主要技术参数 Main technical specifications

型号 Model	最高缝速 Max. sewing speed	线迹长度 Stitch length	针杆行程 Needle bar stroke	挑线杆行程 Thread take-up lever stroke	压脚提升 Presser foot lift	压脚交互量 Presser foot alternation	机针 Needle size	缝台筒径 Bed size in dia.	润滑方式 Lubrication	电动机 Motor
GC2698-1	2400 r.p.m.	0-6 mm	33.4 mm	59.6 mm	手动 / 膝控 By hand / knee 5 / 16 mm	5 mm	DP × 35LR 14*~18*	47 mm	手工润滑 Manual	370 瓦缝纫机专用电机 370W Clutch motor
GC2698-1B	2400 r.p.m.	0-6 mm	33.4 mm	59.6 mm	手动 / 膝控 By hand / knee 5 / 16 mm	5 mm	DP × 35LR 14*~18*	47 mm	手工润滑 Manual	370 瓦缝纫机专用电机 370W Clutch motor
GC2698-2	2400 r.p.m.	0-6 mm	33.4 mm	59.6 mm	手动 / 膝控 By hand / knee 5 / 16 mm	5 mm	DP × 35LR 14*~18*	47 mm	手工润滑 Manual	370 瓦缝纫机专用电机 370W Clutch motor
GC2698-1D	2400 r.p.m.	0-6 mm	33.4 mm	59.6 mm	手动 / 膝控 By hand / knee 5 / 16 mm	5 mm	DP × 35LR 14*~18*	47 mm	手工润滑 Manual	220 伏 550 瓦伺服电机 220V550W Servo motor
GC2698-1Z	2400 r.p.m.	0-6 mm	33.4 mm	59.6 mm	手动 / 膝控 By hand / knee 5 / 16 mm	5 mm	DP × 35LR 14*~18*	47 mm	手工润滑 Manual	220 伏 750 瓦伺服电机 220V750W Servo motor

HARI CHAND ANAND & CO

Corporate Head office: A-94/1, Okhla Industrial Area Phase II, New Delhi - 110020

+91 8584068564 | enquiry@grouphca.com

