

## JT-895/896N

自动开袋机

Automatic pocket welting machine



用于西裤、西装、休闲裤的平行袋(带袋盖)缝制。

双嵌条和单嵌条的切换可以通过操作板的按键一键完成。

扩大了缝制长度(最短18mm -最大220mm)

Used for sewing parallel lines of trousers, suits, slacks (with pocket cover)

The switch between double and single inlay can be completed with one key on the operating board

Extended sewing length (min 18mm-max 220mm)

| 型号            | Model number                          | JT-895   | JT-896N   |
|---------------|---------------------------------------|--|---|
| 袋盖规格          | Pocket cover specification            | 平行袋盖<br>Parallel pocket cover  | 平行袋盖, 斜袋盖<br>Parallel pocket cover, Slant pocket cover  |
| 缝制速度          | sewing speed                          | 最快3000针/分钟 (1000-3000针/分钟)<br>Max.3000 sti/min(1000-3000sti/min)   |   |
| 开袋种类          | Pocket opening types                  | 平行双嵌条, 平行单嵌条<br>(袋盖、无袋盖)<br>Parallel double inlays, parallel single inlay<br>(with pocket cover, without pocket cover)                                       | 平行双嵌条, 平行单嵌条<br>斜双嵌条, 斜单嵌条(袋盖、无袋盖)<br>Parallel double inlays, parallel single inlay, Slant double inlays,<br>Slant single inlay (with pocket cover, without pocket cover) |
| 针距长度          | Stitch length                         | 标准2.5mm (2.0-3.4mm) Standard size 2.5mm (2.0-3.4mm)  |   |
| 缝制长度<br>(固定缝) | Stitch length fastening stitch        | 安全缝: 标准 Safety sewing: standard 1.0mm (0.5-1.5mm)<br>倒缝: 标准 Reverse sewing; standard 2.0mm (0.5-3mm)<br>可转换为安全缝/倒缝 Transfer to safety sewing /reverse sewing |   |
| 角刀调整方式        | Corner-knife cutting adjusting method | 机械式调整<br>Mechanical adjustment   | 电子式调整<br>Electronic adjustment  |
| 使用机针          | Needle                                | DPX17 #16(#14-#18)   |   |
| 缝制花样数         | Number of patterns                    | 99花样 (使用CF卡可以达到999花样)<br>99 types patterns (use CF card can reach 999 types patterns)  |   |
| 循环花样数         | Number of cycle sewing patterns       | 20花样<br>20 types patterns  |   |
| 交互花样数         | Number of alternate sewing patterns   | 20花样<br>20 types patterns  |   |
| 使用机头          | Machine head                          | 双针平缝机<br>Double needle lockstitch machine  | 带停针功能的双针平缝机<br>Double needle lockstitch machine with needle stop function   |
| 针幅            | Needle gauge                          | 8、10、12、14、16、18、20mm<br>22、24、26、28、30、32mm   | 8、10、12、14、16、18、20mm   |