

JT-P900

第六代新款自动拍绒拍棉机
Auto down flapping machine

JT-P900A

A款经典型-带上下吸风除尘,
可选配去静电, 可选配输送机

A classic model - with up and bottom
suction dust removal,
Antistatic function and conveyor(optional).

JT-P900B

B款经济型-带下吸尘

B Economy Model -with bottom air suction



间歇传送, 拍绒/棉更平整

Intermittent transmission, flapping cotton more flat



功能介绍

- 1: 羽绒, 棉, 压花压胶等纺织品填充物的拍散平整;
- 2: 绒棉回收功能, 通过吸风模式把飘散的绒棉吸收回收袋;
- 3: 除静电功能(可选)。

3倍人工效率

普通羽绒裁片: 12000-15000/天 (人工的3倍);

棉织品: 1500-2000件/天 (人工的3倍)。

间歇传动模式送料

当拍杆下落拍散棉充物及羽绒时, 传送带静止不动。当拍杆完成拍
打动作回升抬起拍杆脱离物料时, 传送带开始送料。

本设计极为合理, 避免了拍散物料的同时传送带连续运转造成对
面料的拉扯及损伤。

拍打适应范围广

1. 羽绒类: 90绒, 80绒, 70绒, 50绒, 手抓绒, 飞丝, 毛杆等七大类。
2. 棉类: 机充棉, 珍珠棉, 羽绒棉, 仿丝棉, 手塞棉等五大类。拍的动, 拍的散,
拍的均匀。
3. 复杂类花型: 压花压胶充绒, 曲线, V字, 梯形, 压花压胶充棉的简易花型。

左右对称均衡拍打方式

拍打力度的多样性对羽绒, 棉更散, 更匀称。

Function Introduction:

- 1: Flapping flat on down feather, cotton, embossing and pressure glue and other
textile fillings products
- 2: Cotton recovery function, through the suction to absorb the floating cotton recycling to bag
- 3: Antistatic function (optional).

High efficiency: 3 times than labor work

Ordinary down jacket cut-parts: 12000-15000 pcs/day (3 times than labor work)

Cotton fabric: 1500-2000pcs/day (3 times than labor work)

Intermittent transmission mode feeding

When the rod falls to flap the cotton filling and down jacket, the conveyor belt is
stationary. When the rod completes the flapping action, it rises and lifts away from the
material, and the conveyor belt begins to feed the material.

The design is very reasonable, avoiding the continuous operation of the conveyor belt
while the material is dispersed, which causes the pulling and damage to the fabric.

Widely range of flapping

1. Down jacket: 90 velvet, 80 velvet, 70 velvet, 50 velvet, hand velvet, fly silk, Wool
rod and other seven categories.
2. Cotton: machine-filled cotton, pearl cotton, down jacket cotton, imitation silk cotton,
hand stuffed cotton and other five categories. Flapping even and smooth.
3. Complex type patterns: embossing and glue filling cotton, curve, V type, trapezoid,
embossing and glue filling cotton simple patterns.

Bilateral symmetry flapping method

Different level of flapping strength, down & cotton more disperse and well-balanced.

型号 Model number	除尘方式 Dust clean method	电压 Voltage	功率 Power	电机转速 Motor speed	吸风电机 Suction motor	传动速比 Transmission ratio	G去静电 G destaticizing	H输送机 H transmitting mechanical	整机尺寸 Total size	净重 Net weight
JT-P900A	上下吸风除尘 Up & down suction dust clean	220V	2.2KW	1400r/min	0.4KW	1/7	可选 Optional	可选 Optional	230×145×150CM	460KG
JT-P900B	下吸尘 Lower dust suction	220V	2.2KW	1400r/min	0.2KW	1/7	不可选 Non-optional	不可选 Non-optional	230×145×150CM	420KG