

JTA3B-07

自动袖衩机 (衬衫专用)

Automatic sleeve
slitting machine(For shirt)



实物应用 Real Applications



产品特点 Features

1. 缝纫机机头X轴方向运动,袖衩模具Y轴方向运动,可以满足缝制的精度。
The sewing machine head moves in the X-axis direction and sleeve mold moves in the Y-axis direction, which can meet the sewing accuracy.
2. 袖衩模具结构,可实现快速换款。
Sleeve mold structure can make change quickly.
3. 下托磁性装置,可以提高袖衩折叠的稳定性。
The lower support magnetic device can improve the stability of the sleeve folding.
4. 电子随动辅助压脚装置,保证了缝制的稳定性。
Electronic follow-up auxiliary presser foot device to ensure the stability of sewing.
5. 适用面料广泛(普通衬衫面料、免烫衬衫面料、针织类面料等)。
Wide range of applicable fabrics(Ordinary shirt fabrics, Non-iron shirt fabrics, Knitted fabrics, etc).
6. 一台机可实现左右袖衩切换缝制,无需另制模具。
One machine can realize switching between left and right sleeves, No need to make additional molds.
7. 可加工袖衩长度: 50-200mm, 最宽50mm, 最窄18mm。
Machinable sleeve length: 50-200mm, Maximum width: 50mm, Minimum width: 18mm.

型号	Model number	JTA3B-07
搭载机头	Machine head	兄弟-7300(brother)
工作范围	The scope of work	500mm×280mm
功率	Power	2kw
使用电源	Power supply	AC 220V 50/60HZ (必须接地线Ground wire)
使用气压	Air pressure	0.5Mpa(5kgf/cm ²)
针距	Needle gauge	0.5-2.0mm
控制系统	Control system	单片机控制MCU control
缝纫机转速	Sewing speed	3000 rpm
机器重量	Machine Weight	395KGS
机器尺寸	Machine size	1400×1070×1270mm